
OMNITRONIC Système actif MAXX-1810DSP 2.1

Système PA actif très puissant et DSP, Bluetooth, 800 W (sub 18", tops 10")



Description:

The MAXX-1810DSP is an active 2.1 PA system with 800 watts of continuous power (1600 watts peak) and 123 dB maximum SPL capability. It provides perfect sound and good level stability in various kinds of mobile PA applications.

The high-power 18" subwoofer with power-efficient Class D amplifier in a bass reflex cabinet delivers powerful, dry bass. The two satellite loudspeakers with 10" bass/midrange drivers and 1" compression drivers are equipped with a passive 2-way crossover including PTC tweeter protection and ensure a well-rounded sound experience.

Equipped with a DSP (digital signal processor) which enables convenient application presets for quick sound contouring, the MAXX-1810DSP offers combined XLR and 6.3 mm inputs with XLR parallel output (for linking additional systems), and an additional RCA input with level adjustment. Enjoy music wirelessly from your smartphone or any other Bluetooth device via the integrated Bluetooth audio receiver and charge them at the same time via the integrated powerbank.

The MAXX-1810DSP subwoofer's professional hardware includes a rugged multiplex/MDF enclosure, scratch-resistant lacquer, steel grille and ergonomically shaped handles. Swivel castors for easy transport are optionally available. Matching speaker stands, distance tubes, and stand forks are also available as accessories.

Caractéristiques:

Système PA actif très puissant et DSP, Bluetooth, 800 W (sub 18", tops 10")

- Pour des domaines d'application tels que: Usage portable

L'étendue des fournitures

Logistique

EAN / GTIN: 4026397676921

Poids: 83,35 kg

Longueur: 0.80 m

Largeur: 0.60 m

Hauteur: 1.00 m

Article encombrant

- 1 x mode d'emploi, 2 x tête d'ampli, 1 x câble secteur/câble d'alimentation, 2 x câble d'enceinte, 1 x basse, 1 x déclaration de conformité, 1 x ceinture

OMNITRONIC MAXX-1810 2 voies Top 2x

2 x enceintes large bande passives 10", 150 W RMS

- 2-way bass-reflex system with 10" bass-midrange speaker and 1" compression driver
- Serve as a mobile 2.1 system together with the MAXX-1810 subwoofer
- With passive 2-way crossover, PTC tweeter protection
- Stable MDF enclosures (16 mm) with scratch-resistant lacquer surface, steel grille and recessed handle
- Flange for stand installation
- M8 threaded inserts for suspended installation
- Applications: standing, as monitor, on a subwoofer or speaker stand, suspended

L'étendue des fournitures

- 2 x tête d'ampli, 2 x câble d'enceinte

OMNITRONIC Subwoofer actif MAXX-1810DSP 2.1

Subwoofer actif hautes performances 18" avec DSP et Bluetooth, 800 W

- 18" subwoofer with Class D amplifier in bassreflex cabinet
- Amplifier power: 500 W RMS + 2 x 150 W RMS for two satellites
- Serves as a mobile 2.1 system together with MAXX-1810 2-way tops
- Balanced signal input XLR/6.3 mm jack L/R
- Additional stereo RCA input, with level switch
- Parallel XLR output for linking further active speaker systems
- Integrated Bluetooth audio streaming
- 3 EQ presets with indicators
- Signal limiter, DSP-controlled
- Separate volume control for subwoofer and satellites
- Stereo/mono selection
- MPX/MDF enclosure (16 mm) with scratch-resistant lacquer surface and steel grille
- M20 metal flange for mounting top speakers
- Processeur de signal numérique
- Commandé via Bluetooth
- Rouleaux facultatifs

L'étendue des fournitures

- 1 x mode d'emploi, 1 x câble secteur/câble d'alimentation, 1 x basse, 1 x déclaration de conformité, 1 x ceinture

Données techniques:

Poids: 52,65 kg

OMNITRONIC MAXX-1810 2 voies Top 2x

Capacité de charge:	Programme: 300W Nominale: 2x 150W RMS
Plage de fréquence:	90 - 18000 Hz
Sensibilité:	93 dB
Pression acoustique max.:	119 dB
Dispersion:	90° x 60°
Impédance:	4 Ohm
Connexions:	Entrée: Enceinte via 1 x Boîtier d'enceinte encastrable (F)

Enceinte:	1 x Boumeur (10") env. 25 cm 1 x Pilote de compression aigus (1") env. 2,5 cm
Type d'enceinte:	Boîtier compact
Dimension:	Largeur : 28,5 cm Profondeur : 28,8 cm Hauteur : 46,6 cm
Poids:	19,95 kg

OMNITRONIC Subwoofer actif MAXX-1810DSP 2.1

Capacité de charge:	Nominale: 500W RMS LF Nominale: 2x 150W RMS HF
Alimentation électrique:	230 V AC, 50 Hz
Puissance totale de raccordement:	800 W
Plage de fréquence:	32 - 190 Hz Basse 90 - 18000 Hz Tête d'ampli
Sensibilité:	99 dB
Pression acoustique max.:	123 dB
DSP:	Processeur de signal numérique
Commande:	Bluetooth
Commutation:	Class D
Connexions:	Entrée: Stéréo via 1 x RCA stéréo Entrée: Stéréo via 1 x Câble jack XLR/6,35 mm 3 broches (F) prise combo version encastrable Sortie: Line via 1 x XLR 3 broches Sortie: Enceinte via Boîtier d'enceinte encastrable (F)
Entrée des canaux:	1 x Stéréo via XLR ou RCA ou Bluetooth, réglage du canal via Bouton rotatif
Enceinte:	1 x Boumeur (18") env. 45 cm avec Aimant en ferrite
Type d'enceinte:	Subwoofer
Type de construction:	Bassreflex
Aide au transport:	Rouleaux facultatifs
Matériau:	Bois multiplex bouleau; MDF (panneaux de fibres à densité moyenne)
Dimension:	Largeur : 50,4 cm Profondeur : 60,8 cm Hauteur : 46,6 cm
Poids:	32,70 kg